

Scientific / Metrology Instruments

High Performance Gas Chromatograph - Time-of-Flight Mass Spectrometer

Solutions for Innovation

Comprehensive 2D GC coupled with JEOL GC-HRTOFMS: GCxGC Applications



JEOL Ltd.


Diesel Fuel Analysis by GCxGC/EI


Hydrocarbon Classification

Comprehensive two-dimensional gas chromatography (GCxGC) consists of two different types of columns that are connected via a thermal modulator within the same GC oven. The GCxGC system requires a fast-acquisition detection system to measure the very narrow width peaks observed in the 2D GC chromatograms. The JEOL GC-TOFMS system called "the AccuTOF $^{\rm TM}$ GCx" has a high-speed data acquisition capability with a spectral acquisition rate of up to 50 Hz (0.02sec/spectrum).

Therefore, the $AccuTOF^{TM}$ GCx system can be successfully used as a GCxGC detector.

The TIC chromatograms for crude oil and 2 diesel fuels are shown on the left. Each sample shows a number of different compounds and different hydrocarbon distributions. As this data shows, GCxGC is a powerful separation technique for analyzing complex samples like oils and fuels.







Biomarker Analysis by GCxGC/PI


Target Analysis using 2D EICC

Both GCxGC/PI and GCxGC/EI measurements for crude oil samples were done using the EI/PI combination ion source. Each GCxGC measurement showed a number of biomarkers that included Steranes and Triterpenes. The PI mass spectra for these biomarkers showed strong molecular ion signals which were used to make high-selectivity (narrow *m/z* window) 2D extracted ion chromatograms (EIC) for quick identification of these compounds. Afterwards, these results were further confirmed by using NIST library database searches of the GCxGC/EI data.



Pl mass spectra





2D-PI chromatograms: Upper: TIC, Lower: EIC

Type Analysis by GCxGC/FI

Hydrocarbon Type Analysis

Comprehensive GCxGC in combination with high-resolution mass spectrometry (HRMS) is a powerful tool for the analysis of complex mixtures. Field ionization (FI) is a soft ionization technique that is well suited for hydrocarbon analysis because it generates molecular ions for most compounds with minimal fragmentation. This data easily provides individual hydrocarbon information (formula, carbon number, intensity) by using the molecular ions that are generated by FI. As a result, it is not necessary to use complex El fragmentation information for petroleum type analysis measurements. The key advantages of GCxGC/FIHRMS method for detailed type analysis of petroleum samples are:

1. Fl is ideal for generating molecular ions for hydrocarbon compounds.

- 2. High selectivity (with narrow m/z windows) allows highprecision 2D extracted ion chromatograms.
- 3. GCxGC provides exceptional separation capacity with 2D structure-retention relationships.

FI is ideal for hydrocarbon compounds FI can generate molecular ions with minimal fragmentation. This makes it easy to identify the parent ion for each hydrocarbon n-C₁₆H₃₄ n-C₃₀H₆₂ FI mass spectra of n-Alkanes

High selectivity extracted ion chromatograms (EIC)

High mass resolution can provide high

The hydrocarbon peaks which have the same nominal mass but different exact mass can be separated completely.







GCxGC/FI EIC of m/z 184.1253 (C₁₄H₁₆)

GCxGC provides exceptional separation


Although the AccuTOF™ GCx has excellent high mass resolution capabilities, some components are difficult to separate. For example, the separation between PAHs (C₁₆H₁₂) and Benzothiophenes $(C_{13}H_{16}S)$ requires over 180,000 mass resolution. Despite the fact that the AccuTOFTM GCx does not have this high of a mass resolution, these groups can be clearly separated in time on the 2D EIC. As a result, we can ensure that only the actual components of interest are included in each polygon.



GCxGC/FI EIC of m/z 204.0939



Type analysis templates of 13 hydrocarbon series: $C_nH_{2n+2},\ C_nH_{2n},\ C_nH_{2n-2},\ C_nH_{2n-4},\ C_nH_{2n-6},\ C_nH_{2n-8},\ C_nH_{2n-10},$ $C_nH_{2n\text{-}12},\,C_nH_{2n\text{-}14},\,C_nH_{2n\text{-}16},\,C_nH_{2n\text{-}18},\,C_nH_{2n\text{-}20}\text{ and }C_nH_{2n\text{-}22}$



Key Technology -Soft Ionization-

A wide variety of soft ionization techniques from JEOL!


Soft ionization provides higher intensity molecular ion information than Electron Ionization (EI), the typical hard ionization method.


The JEOL GC-TOFMS system offers a wide variety of ionization methods. You can choose the most suitable soft ionization technique for your applications!

- Chemical Ionization (CI): Available with both positive and negative ion modes
- Field Ionization (FI): Softest ionization method
- Photoionization (PI): Soft ionization and sensitive for aromatic compounds
- Low energy EI (LE-EI): Available by adjusting the electron energy to lower voltages using the standard El source.

[FI/FD]

Field Ionization (FI) and Field Desorption (FD) are well suited for hydrocarbons analysis because they generate molecular ions for almost all compounds, including saturated hydrocarbons, with minimal fragmentation. The ionization process for these techniques is carried out in the high-potential electric field (~108 V/cm) between the FI/FD emitter (Anode) and the counter electrode (Cathode). A molecular ion is formed within the highpotential electric field when an electron from the analyte molecule tunnels rapidly towards the emitter. The resulting mass spectra are dominated by molecular ions, whether from the GC output (FI) or from the emitter surface (FD).








Synthetic Polymer Analysis by Pyrolysis GCxGC/EI and FI


Unknown Compounds Analysis in Nylon 66

The pyrolysis of Nylon 66 showed an unknown compound that did not show a reasonable match in the NIST database for the EI mass spectrum. The FI mass spectrum showed a molecular ion that was not present in the EI mass spectrum. Using the molecular ion accurate mass, an elemental composition was calculated. Afterwards, a chemical structure was suggested using the fragment ion information in the EI mass spectrum.












Suggested unknown component

Additives Analysis by Pyrolysis GCxGC/EI and FI

Targeted Additives Analysis in Nitrile Butadiene Rubber








The characteristics of polymeric materials vary depending on the additives. Consequently, a variety of additives can be added into the raw polymer resin in order to achieve the required characteristics for the product. In this study, we identified the additives for a commercially available molded polymer, nitrile butadiene rubber using GCxGC/EI and GCxGC/FI.

The results showed that:

- Additives such as benzothiazole in the polymer material were easily separated chromatographically by using the GCxGC technique.
- The EI mass spectra produced good matches with the NIST library search which were further supported by the FI accurate mass elemental composition calculations for the molecular ions. These data, used together, were effective for qualitative identification of the additives.



2D-El and Fl TIC chromatograms


Natural Polymer Analysis by Pyrolysis GCxGC/EI and PI


Powerful Separation of the Main Components in a Japanese Lacquer Film

A Japanese lacquer film called "Urushi" is a natural polymer that has been used as a paint and adhesive for living-wares and craft-wares for approximately 8,000 years. In this work, we measured "Urushi" samples using this unique Pyrolysis/ GCxGC/TOFMS system in combination with our new combination EI/PI ion source.



"Urushi" picking (left) and traditional crafts coated with "Urushi" (right).






2D-TICCs of FI data and PI data


The sample was analyzed by both Py-GCxGC/El and Py-GCxGC/PI using a pyrolysis temperature of 500°C.

Afterwards, the El data was used to construct a 2-dimensional extracted ion chromatogram (2D-EIC) for m/z 123.044 ($C_7H_7O_2$), a common fragment ion for alkyl catechols (R-C₆H₃(OH)₂). This 2D-EIC made it easy to identify two series of compounds, one for the alkyl catechols and one for the alkyl oricinols.

Subsequently, the PI mass spectra were checked for the main components, i.e., 3-Pentadecyl catechol and 3-Pentadecenyl catechol. Pl is a soft ionization method that produced strong molecular ions for many of the compounds in the sample. The accurate masses of these ions were used to determine the elemental compositions for these compounds.



2D-EIC using m/z 123.0441 (C₇H₇O₂)±0.01 with EI data




Key Technology -Combination Ion Sources-

Two Optional Combination Ion Sources - EI/FI/FD and EI/PI -

The EI/FI/FD combination ion source is a unique option that is only offered on the JEOL AccuTOFTM GCx system. El and FI/FD modes can be switched by simply exchanging the El repeller probe and the FI/FD emitter probe, without breaking vacuum. As a result, both GCxGC/El and GCxGC/Fl measurements can be done (along with FD) using a single ion source.

Additionally, JEOL offers an El/Photoionization (PI) combination ion source for the AccuTOF[™] GCx. While FI is still the softest ionization technique available, PI can also be used to generate molecular ions for hydrocarbons. In particular, aromatic hydrocarbons, which strongly absorb UV light, are preferentially ionized with PI, making the technique useful for detecting aromatic hydrocarbons in complex mixtures. In this case, each method is available by turning on the filament for El or the UV lamp for PI. As a result, both GCxGC/EI and GCxGC/PI measurements can be done using a single ion source.



Soluble Organic Fraction Analysis by GCxGC/EI

Analysis of PAHs in Exhaust Gas

Particulate material collected from exhaust gas was extracted into an organic solvent. The GCxGC/El data shows that the PAHs were well separated from the saturated hydrocarbons,


2 stroke engine vehicle

Aromatic hydrocarbons

Saturated hydrocarbons

2D-EI TIC chromatogram

which have the same 1st column retention time. The PAHs were then identified using a NIST database search with the EI mass spectra.



El mass spectrum

Electronics Waste Analysis by GCxGC/El and Negative Cl

Halogenated Compounds Analysis

Dust samples collected from an electronics recycling facility were extracted into organic solvent and then analyzed by using GCxGC/El and GCxGC/Cl. The chlorinated and brominated compounds were identified by using acombination of Kendrick mass defects (KMD) and 2D mass chromatograms. The NIST library search results and accurate mass measurement results from the data acquired in El mode were used to identify each compound in each series.

This combination of library search and elemental composition determination is a very powerful tool for detailed qualitative analysis.


Electron capture (often called "negative ion CI or NICI") measurements with GCxGC were investigated using KMD

analysis. Generally, each compound showed a strong molecular ion that agreed with the El data. However, several compounds showed abundant Cl⁻ and Br⁻ peaks instead of molecular ions. The NICl method is effective for the analysis of low-concentration samples and quantitative analysis.


Reference:

- [1] Karl J. Jobst, et al. *The use of mass defect plots for the identification of (novel) halogenated contaminants in the environment,* Anal Bioanal Chem (2013) 405:3289–3297
- [2] Masaaki Ubukata, et al. Non-targeted analysis of electronics waste by comprehensive two-dimensional gas chromatography with high-resolution mass spectrometry:

Using accurate mass information and mass defect analysis to explore the data, Journal of Chromatography A,(2015) 1395, 152-159.



2D-El chromatograms: Upper: TIC, Lower: EIC



2D-Negative CI chromatograms: Upper: TIC, Lower: EIC

Aroma Oil (Fragrance) Analysis by GCxGC/El and Fl

Molecular ion detection for Alcohol compounds


Aroma oils are a complex mixture of chemical compounds that include alcohols, terpenes, esters, etc.

Typically, alcohol compounds easily decompose during El measurement, thus making it difficult to measure their molecular ions. As a result, the NIST database search for each El mass spectrum will not necessarily show a good match for these compounds.


Therefore, it is important to use a soft ionization technique to confirm the molecular ions.

In this work an aroma oil was analyzed by both GCxGC/El and GCxGC/Fl. An El and Fl mass spectrum are shown for a representative diol and triol compound.


The EI mass spectra for these compounds do not show their molecular ions. However, the FI mass spectrum for each alcohol shows a high intensity molecular ion peak.



2D TIC chromatograms



El and Fl mass spectra of a diol compound



El and Fl mass spectra of a triol compound


Sebum Analysis by GCxGC/EI


Pharmaceutical application

Skin is an active metabolic tissue that synthesizes a variety of lipid compounds.

Sebum, an oily material secreted by the skin, is known to provide moisturizing effects, sun light protection, and antibacterial protection for the skin surface. The sebum consists of a complex mixture of free fatty acids, squalene, cholesterol, wax esters, diacylglycerols, and triacylglycerols. These species and their concentrations vary depending on skin conditions.

The 2D GC conditions resulted in high chromatographic separation of the lipid compounds from low boiling point fatty acids up to high boiling triglycerides in a single measurement. Additionally, these lipid compounds were comprehensively identified using a combination of accurate mass measurements and NIST library searches by HRTOFMS. As an example, peak [A] was matched to oleic acid using a NIST library search. Furthermore, this mass spectrum showed a molecular ion that coincided with the calculated accurate mass of oleic acid (error of 1.4 mDa). Peak [B] was matched to triolein using an NIST library search, and the characteristic high m/z ion was matched to the calculated accurate mass of $C_{35}H_{67}O_4$ which is a characteristic fragment ion of triolein (error of 1.1 mDa).





*Specifications subject to change without prior notice.

Certain products in this brochure are controlled under the "Foreign Exchange and Foreign Trade Law" of Japan in compliance with international security export control JEOL Ltd. must provide the Japanese Government with "End-user's Statement of Assurance" and "End-use Certificate" in order to obtain the export license needed for export from Japan. If the product to be exported is in this category, the end user will be asked to fill in these certificate forms.

Zoex's GCxGC system is provided and supported thorough Zoex's sales and support network and may not be available in your territory. Contact your local JEOL representative for detail.



3-1-2 Musashino Akishima Tokyo 196-8558 Japan Sales Division Tel. +81-3-6262-3560 Fax. +81-3-6262-3577 www.jeol.com ISO 9001 • ISO 14001 Certified

**AUSTRALIA & NEW ZEALAND / JEOL (AUSTRALASIA) Pty, Ltd., Suite 1, L2 18 Aquatic Drive - Frenchs Forest NSW 2086 Australia **BELGIUM / JEOL (EUROPE) B.V. Planet II, Gebouw B Leuvensesteenweg 542, B-1930 Zaventem Belgium **BRAZIL / JEOL Brasil Instrumentos Cientificos Ltda. Av. Jabaquara, 2958 5° andar conjunto 52; 04046-500 Sao Paulo, SP Brazil **CANADA / JEOL CANADA, INC. 3275 Tere Rue, Local #8 SH-Hubert, QC J3Y-8Y6, Canada **CHINA / JEOL (BELJING) CO., LTD. Zhongkeziyuan Building South Tower 2F. Zhongguancun Nansanjie Street No. 6, Haiciian District, Beijing, P.R. Fichina **EGYPT / JEOL SERVICE BUREAU 3rd FI. Nile Center Bidg., Nawal Street, Dokki, (Cairo), Egypt **FRANCE / JEOL (EUROPE) SAS Espace Claude Monet, 1 Alle de de Giverny 78290, Croissy-sur-Seine, France **GERMANY / JEOL (GENAMY) GEND (GENAMY) / JEOL (LORGE ALTO, LORGE A

No.2051L781C(Bn)