

ACQUITY PREMIER TUV Detector

The Waters™ ACQUITY™ PREMIER Tunable UV (TUV) Detector is a tunable, dual-wavelength UV/Visible (UV/Vis) detector specifically designed and optimized for the entire line of ACQUITY PREMIER systems. The ACQUITY PREMIER TUV Detector's innovative light-guiding flow cell design and High Brightness Lamp are each equipped with Intelligent Chip Technology, allowing for the electronic recording of pertinent component information flow, which is then viewable within the Empower™ Software database and available for inclusion in a comprehensive status report. Additionally, the design of the ACQUITY PREMIER TUV Detector allows for reduced sensitivity to laboratory environmental fluctuations, such as temperature and humidity changes. The ACQUITY PREMIER TUV Detector maintains its low-noise electronics and support for sampling rates up to 80 points/s.

OPERATING SPECIFICATIONS¹

Wavelength range	190 to 700 nm
Wavelength accuracy	±1 nm (via patented ² Erbium filter)
Linearity range	Deviation at 2.5 AU ≤5%, propylparaben, at 257 nm
Baseline noise ³	6 x 10 ⁻⁶ AU, at 230 nm, 10 mm shunt cell, 1.0 second filter time constant
Drift	≤5.0 x 10 ⁻⁴ AU/hour/°C at 230 nm
Sampling rate	Up to 80 points/s
Unattended operation	Leak sensors, full diagnostic data captured through console software

OPTICAL COMPONENT SPECIFICATIONS

Light source	Prealigned, intelligent technology deuterium lamp (Warranty for one year or 2000 hrs, whichever comes first)
Dispersion volume	≤0.8 µL (Analytical flow cell) ≤1.5 µL (High sensitivity flow cell)
Flow cell design	Light-guiding UPLC™ flow cell with Intelligent Chip Technology
Path length	10 mm (analytical flow cell)
Cell volume	500 nL (analytical flow cell)
Pressure limit	1000 psi (all flow cells)
Wetted materials	316 stainless steel, fused silica, Teflon® AF, PEEK (analytical flow cell)
Optical bandwidth	5 nm

PHYSICAL/ENVIRONMENTAL SPECIFICATIONS

Dimensions	Width: 34.3 cm (13.5 inches) Height: 19.3 cm (7.6 inches) Depth: 60.9 cm (24.0 inches)
------------	--

Weight	12.0 kg (26.5 pounds)
Operating temperature range	4 to 40 °C (39 to 104 °F)
Operating humidity range	20% to 80%, non-condensing
Compliance	CE Mark CSA C-tick and UL
Audible noise	≤58 dBa

ELECTRICAL SPECIFICATIONS

Power requirements	100 to 240 VAC
Line frequency	50 to 60 Hz
Power consumption	185 VA (nominal)
Inputs	One input (inject start)
Outputs	Two outputs (one event, one analog)

OPTIONAL FLOW CELLS

Analytical	500 nL volume, 10 mm pathlength
High sensitivity	2400 nL volume, 25 mm pathlength

DETECTOR ORDERING INFORMATION	PART NUMBER
ACQUITY PREMIER TUV Detector	176018010
ACQUITY UPLC ID Cell TUV, Analytical TAF HPS	205002268
ACQUITY UPLC Cell TUV, 25mm, Teflon AF	205015018

1. All specifications derive from instrument performance after a 1-hour warm-up time.
2. US Patent Numbers: 6,423,249 and 6,783,705.
3. ASTM Standard E1657.

Waters

THE SCIENCE OF WHAT'S POSSIBLE.™

Waters, The Science of What's Possible, ACQUITY, UPLC, PREMIER, and Empower are trademarks of Waters Corporation. All other trademarks are the property of their respective owners.

©2020 Waters Corporation. Produced in the U.S.A. November 2020 720007057EN LM-PDF

Waters Corporation
34 Maple Street
Milford, MA 01757 U.S.A.
T: 1 508 478 2000
F: 1 508 872 1990
www.waters.com