

DataApex SW – Comparison table

	Clarity	Clarity Lite	CSW32	CSW17
Architecture	Multi-instrument 4 Instruments - each up to 32 channels	Single instrument, Up to four channels	Multi-channel Up to four channels	Multi-channel Up to four channels
Multi-detector Measurement	Yes Up to 12 independent detectors on each instr.	Yes Up to 4 detectors	No	No
Windows System	32 bit, 64 bit (from Clarity ver. 3.0)	32 bit, 64 bit (from Clarity Lite ver. 3.0)	32 bit	16 bit
GLP/21 CFR Part 11	Password protection & expiration, electronic signatures, audit trail, user accounts with access rights	No	Password protection, accounts with access rights, log file	Password protection, accounts with access rights
Extensions	GPC, PDA, SST, CE, EA, NGA, DHA, MS	No	SST	SST (external)
Controls	GC, LC, AS, Valve, Balance, Detectors, PDA	No	GC, LC, AS	GC, LC, AS
Auxiliary programs	Validation Kit, Test IQ	No	Test IQ	No
Summary Table	Yes	Yes	No	No
Data Export	ASCII, AIA, dBase	ASCII, AIA, dBase	ASCII, AIA, dBase	ASCII
Multiple ISTD	Yes (from Clarity ver. 5.0)	Yes (from Clarity Lite ver. 5.0)	No	No
Data Import	CSW32/17, ASCII, AIA	CSW32/17, ASCII, AIA	CSW 17, ASCII, AIA	ASCII, AIA by external program
Min. resolution of monitor	1024x768, 64k colors	1024x768, 64k colors	1024x768, 64k colors	800x600, 256 colors
Available HW *	All DataApex HW (any combination)	Colibrick, U-PAD2, U-PAD, INT9, INT7	INT7, INT5, U-PAD, CB20, CB11	INT7, INT5, CB11
Method history in Chromatogram file	Including a copy of calibration file	Including a copy of calibration file	No	No
Batch Reprocessing	Yes	No	Yes	Yes
Print Preview	Yes	Yes	Yes	No
Archive/Restore	Yes	No	Yes	Yes
Support	Full support, Automatic Update from Web	Full support, Automatic Update from Web	Obsolete product, limited support, Upgrade to Clarity recommended	Obsolete product, limited support, Upgrade to Clarity recommended

* refer to datasheet D016 - HW x SW x OS compatibility table