

TOY20DAD 800 I

TWO CHANNEL UV DETECTOR
FOUR CHANNEL UV DETECTOR
SCANNING UV DETECTOR



is **OEM built-in** UV detector suited for preparative and flash chromatography with diode array (**DAD**) in range **190 – 800 nm**. It is offered in the following versions:

Two Channel version measures at **two wavelengths simultaneously** with possibility to see **current scan**.

Four Channel version measures at **four wavelengths simultaneously** with possibility to see **current scan**.

Scanning version measures at **four wavelengths simultaneously** or **sends scan with speed 20 Hz** which allows to create **3D picture**.

More wavelengths or scan are used in liquid chromatography to **verify purity of analyzed samples** or in situations when some peaks absorb on different wavelengths.

The unit is supplied with **AMY17 PCB** board of dimensions 100 x 160 mm (3.94 x 6.30 in). It powers the lamp and control the unit.

Most important features of TOY18DAD detectors:

- small dimensions
- **built-in lamp working hours counter**
- **easy replacement of flow cell**
- **measuring at more wavelengths simultaneously**
- **sophisticated diagnostic software**

To the AMY17 board can be optionally connected

- Analog outputs board
- LAN and USB board
- Display with keyboard
- Leakage sensor

SPECIFICATION

	TOY20DAD 800 I Two Channel	TOY20DAD 800 I Four Channel	TOY20DAD 800 I Scanning
Part Number	T20I310Y	T20I320Y	T20I330Y
Wavelength range	190 - 800 nm (256 elements on CCD)		
Number of channels (Signals)	2	4	4
Scan	Informative 190 – 800 nm	Informative 190 – 800 nm	190 - 800 nm, 20 Hz, step 1 nm
Typical spectral half-width	10 nm		
Accuracy of adjustment / Reproducibility	± 1 nm /±0.5 nm		
Noise level at test cell (254 nm, TC 0.75s)	± 5 x 10 ⁻⁵ AU		
Drift at test cell (254 nm after 1 h)	1 x 10 ⁻³ AU/hr		
Materials in contact with mobile phase	FEP; fused silica, stainless steel. PEEK		
Time constant (T63)	0.5 s, 0.75 s, 1.0 s, 2.0 s, 4.0 s, 8.0 s, 16.0 s, 0.2 s, 0.1 s		
Interface	RS232; optionally LAN or USB		
Power supply	24 -36 V DC		
Power input	48 W		
Dimensions (W x H x D)	180 x 90 x 70 mm (7.09 x 3.54 x 2.76 in)		
Weight	1.250 kg (2.46 lb)		

PREPARATIVE CELL PLCC15 IN BRACKET (SUPPLIED WITH UNIT)

volume/optical path (adjustable)	45 µl / 0.3 mm; 55 µl / 1.4 mm; 70 µl / 2.4 mm
Cell connecting	tubing with OD = 1/8", thread 1/4"-28
Maximal flow rate	500 ml/min. (3 000 ml/min. with PLCC 3L)