thermo scientific

Productivity redefined

Orbitrap Exploris 120 mass spectrometer





Setting the new standard in productivity

Whether it's method development or everyday testing, accelerate your route to qualitative and quantitative confidence with consistently accurate data delivered by proven Thermo Scientific[™] Orbitrap[™] technology.

Designed for operational simplicity, the Thermo Scientific[™] Orbitrap Exploris[™] 120 mass spectrometer sets the new standard in instrument productivity and ruggedness.



The Orbitrap Exploris 120 mass spectrometer coupled to the Thermo Scientific[™] Vanguish[™] Core HPLC system.

Productivity | Operational Simplicity | Ruggedness

• Take the fast path to high-confidence, high-resolution MS results

Spend less time questioning data and more time finding answers to your most pressing questions. The Orbitrap Exploris 120 mass spectrometer combines superior resolution and mass accuracy with a powerful suite of data analysis tools to provide accurate results for screening and quantitation, and to streamline method development and everyday testing.

Maximize return on investment


Gain peace of mind knowing that your laboratory will keep running smoothly. The Orbitrap Exploris 120 mass spectrometer minimizes time spent on calibration of different mass ranges and on maintenance, while delivering robust performance. For laboratories testing a high volume of samples, fast scanning and polarity switching decrease sample turnaround times.

• Reduce method set-up time

Empower both novice and experienced staff to analyze samples using ready-to-run method templates. Minimize time spent on training using the common data-acquisition user interface shared by next-generation Thermo Scientific Orbitrap Exploris, Thermo Scientific[™] TSQ[™] Triple Quadrupole and Thermo Scientific[™] Orbitrap Tribrid[™] mass spectrometers.

Confidently uncover more analytes of interest

High-resolution mass spectrometers are designed to resolve analytes of interest from interferences. With Orbitrap high-resolution accurate-mass (HRAM) technology, the Orbitrap Exploris 120 mass spectrometer goes further by discriminating ions of interest from interfering ions differing by only very small mass increments at mass-to-charge ratios as low as m/z 40. As a result, you substantially reduce the likelihood of false positives and negatives when analyzing complex sample matrices.



Full-scan mass spectrum of etoxazole and isopyrazam, measured using the Orbitrap Exploris 120 mass spectrometer at a resolution (R) setting up to 120,000 (FWHM) at *m/z* 200, demonstrates outstanding resolving power.

Unknown analysis, non-targeted and targeted screening

Resolve ions of interest from interfering ions with high mass resolution up to 120,000 (FWHM) at *m/z* 200 over the mass range *m/z* 40–3,000.

Confident identification using accurate mass assignments

Determine elemental compositions based on accurate *m/z* values.

Analyte confirmation

Obtain correct assignment of fine isotopes for an additional dimension of information beyond MS/MS fragments, accurate masses, and retention times.

Data mining

Answer ongoing and future questions about specific analytes or groups of new analytes by interrogating full-scan accuratemass data at any time!

Quantify analytes in complex matrices with maximum accuracy

Accurate, optimization-free quantitation

The Orbitrap Exploris 120 mass spectrometer improves data accuracy for quantitation in complex matrices, reliably meeting limits of detection (LODs) with superior resolving power. Orbitrap HRAM technology delivers sub-ppm mass accuracy, enabling accurate, selective detection of target analytes over five orders of linear quantitative dynamic range without detector saturation. Once you choose a scan mode and mass range, no further compound optimization is required.

Level	Concentration	% Diff	% Ion Ratio	% CV		Level	Concentration	% Diff	% Ion Ratio	% CV
		-5.07	pass] [0.80	pass	
Cal1	0.01 ng/mL	-5.64	pass	0.9		Cal7	6.0 ng/mL	1.18	pass	1.0
		-4.62	pass					-0.77	pass	
		0.11	pass] [-2.74	pass	
Cal2	0.02 ng/mL	5.10	pass	5.0		Cal8	10.0 ng/mL	-4.09	pass	1.0
		-9.24	pass					-2.22	pass	
		-5.39	pass		1 [-2.71	pass	
Cal3	0.05 ng/mL	-2.83	pass	0.9		LQC	0.27 ng/mL	0.21	pass	2.3
		-4.59	pass					2.11	pass	
		-0.51	pass		1 [-0.86	pass	
Cal4	0.2 ng/mL	2.01	pass	2.1		MQC	1 ng/mL	-0.74	pass	3.2
		-2.34	pass					-6.25	pass	
		4.74	pass		1 [-0.5	pass	
Cal5	0.8 ng/mL	0.72	pass	1.8		HQC	6.2 ng/mL	-4.44	pass	2.9
		1.79	pass					-5.85	pass	
		11.41	pass		1					
Cal6	3.0 ng/mL	8.49	pass	2.0						
		5.96	pass							

Exceptional linearity over a wide concentration range and a lower limit of quantitation (LLOQ) of 0.01 ng/mL for testosterone in serum demonstrate the ability of the Orbitrap Exploris 120 mass spectrometer to accurately quantify analytes in complex matrices with high reproducibility.

Popular scan modes

Full Scan: Obtain comprehensive data coverage by capturing all ions in a user-defined mass range with high mass accuracy. Extract desired *m/z* values immediately after data acquisition or later using retrospective data analysis.

Targeted Selection Ion Monitoring (t-SIM): Achieve higher sensitivity by setting a narrow mass range (quadrupole as narrow as 0.4 Da).

Targeted-MS/MS (previously parallel reaction monitoring mode):


Gain additional selectivity in complex matrices. A high-resolution product-ion spectrum is only generated for precursor ions detected in a narrow mass range per a mandatory inclusion list.

Keep your laboratory running seamlessly

Frequent unplanned or planned downtime can impede your laboratory's ability to achieve its goals. By minimizing downtime, the Orbitrap Exploris 120 mass spectrometer ensures on-time delivery of your results.

Single, stable calibration procedure for the entire mass range


Access sub-ppm mass accuracy for at least five days with the Thermo ScientificTM EASY-ICTM ion source. With automated internal calibrant delivery, the EASY-IC ion source saves you time so you can quickly return to running your samples. Use the Thermo ScientificTM PierceTM FlexMixTM Calibration solution to perform a single calibration for the full mass range of m/z 40–3,000, in both positive and negative modes.



Through the use of Thermo Scientific EASY-IC ion source, sub-ppm mass accuracy is consistently delivered without user intervention for at least five days. A panel of veterinary drugs with *m/z* range from 160...900 was analyzed at 100 μ g/L over a 15 day period with continual polarity switching, providing exceptional mass accuracy.

Minimal user intervention for servicing

Don't limit your laboratory's productivity with lengthy scheduled maintenance procedures. The Orbitrap Exploris 120 instrument design allows easy access to mass analyzer components, reducing time spent on maintenance.




	Long term system robustness der	monstrated for pesticides	in olive oil over 250 in	jections with polarity switching.
--	---------------------------------	---------------------------	--------------------------	-----------------------------------

Compound name	Average %RSD for 250 injections
Atrazine	1.6
Azoxystrobin	2.0
Bentazone neg	2.5
Bromoxynil neg	1.2
Carbendazim	2.0
Cycluron	1.6
Dicrotophos	2.2
Fluazinam neg	5.5

Gain peace of mind with system-to-system consistency

For organizations that plan to have different users running more than one instrument in the same lab or in different locations, the Orbitrap Exploris 120 mass spectrometer has a demonstrated ability to deliver consistent results across multiple instruments and users.




To assess LC-HRAM MS system-to-system reproducibility, two operators at two different locations analyzed the same sample of veterinary drug residues in bovine muscle matrix on two separate systems. The minimal 5.1% average difference observed in analyte concentrations demonstrate high reproducibility across multiple Orbitrap Exploris 120 mass spectrometer systems.

Decrease sample turnaround times

For laboratories processing a high volume of samples or facing tight deadlines to submit results, the Orbitrap Exploris 120 mass spectrometer quickly generates accurate results, enabling you to meet internal and external client expectations.

Maximize compound coverage with fast scan rates

With a scan rate of up to 22 Hz, the Orbitrap Exploris 120 mass spectrometer triggers more precursor ions for MS/MS analyses, so you can produce results quickly and confidently. Fast scanning also enables you to run shorter UHPLC gradients with excellent resolution, sensitivity, and mass accuracy.




Quantitation of all compounds in bovine muscle matrix is easily achieved by fast scan speeds, even when multiple precursor ion *m/z* isolation windows are selected for the data-independent acquisition (DIA) experiment.

Analyze samples twice as quickly with rapid polarity switching

Process samples faster using positive and negative mode switching in approximately 1.4 Hz cycles. In contrast to other high-resolution instruments, the mass resolution and mass stability of the Orbitrap Exploris 120 instrument does not need to recover after polarity switching, saving valuable analytical time.


Scan	Exact mass	Observed mass	Delta ppm
1	317.1390	317.1386	-1.26
2	317.1390	317.1389	-0.32
3	317.1390	317.1389	-0.32
4	317.1390	317.1390	0.00
5	317.1390	317.1389	-0.32
6	317.1390	317.1391	0.32
7	317.1390	317.1390	0.00
8	317.1390	317.1389	-0.32
9	317.1390	317.1388	-0.63
Avera	age		-0.32

Full-scan MS data acquired for 90 ng/g Zearalenone in corn feed demonstrates preservation of mass accuracy stability during polarity switching.



Deploy Orbitrap HRAM technology for a variety of samples

When it comes to small molecule analysis, many industries face similar challenges. Orbitrap HRAM technology enables laboratories to use novel approaches to emerging contaminant identification, meet increasingly lower LODs, and protect their brand's reputation for product or service quality. Overall, Orbitrap HRAM data provides many industries a faster path to unambiguous answers.



The Orbitrap Exploris 120 mass spectrometer allows us to react to emergency testing situations in a variety of matrices without having to do a lot of method development. This enables us to provide high quality data for veterinary drug residue testing to our clients."

Dwayne Schrunk, Laboratory Manager of the Analytical Chemistry Services, Iowa State University

Focus on driving results with faster method set up

The intuitive Method Editor features a drag-and-drop user-friendly interface with optimized method templates for a wide range of applications, simplifying everyday usability.

Easy, intuitive instrument control

- Single-method control of tune and data-acquisition parameters simplifies error-free operation
- Ready-to-use application-specific templates reduce method development time
- Auto-settings enable quick startup for most experiments
- Drag-and-drop method editing with Tool Tips offers flexibility in an easy-to-visualize format

Method Timelin	rs Scan Parameters	Summary						Experiment ACTIONS V	Settings	
e Method Timelin	10	20	30		40		50	60.	and the second sec	
aration (min)									Infusion Mode	Liquid Chromatography *
aration (min)									Expected LC Peak Width (s	30
									Mild Trapping	D
								Q		
								QQ	Internal Mass Calibration	off
AT Experiment = 1		Time Range (mir	0-60			- 21				
							Properties			
as Template						-				
en Templates	File Orbitrap Explores 120 Method Editor	23.180								Stop Shared
al Research	14 Prote Street int									
	Method Editor	Global Paramoters Scan	Parameters Summary							
ronimental Steroids	A REAL PROPERTY AND A REAL	Method Timeline			-			Experiment	ctions 🖌 🖌 Settings	
			18		6.5	ę.		7.5 9		
d Safety	Method Ducation (trin)			Pro	duction scan				Infusion Mod	Se Diquist Chevenetog
	0								Expected LC	Pearl Width (s) 4
domics +									Q Mid Tuppin	1 D
										Calibration Off
bolomics +									Q Internal Mass	Calbaco Ca
		Experiment = 1	Tanie Kunge (in				мисн 🖆 слык 🗑			
harma	Scara		Perchart (on Scan				ator of sont of	Product Ion Scen Properties		ster
n Suitability	SIM Servi	Compound Po	ornela Added Presserver invizi	Pressence Charge (2) FT Ten	er (mir) Wieldose inte	Golfston Energy M	Polanty	Multiplectors	0	
- Summer y		1 11 ceorgicarticocheriene	(to adduct) / 331.2268	1 49	0.2	85	Pocitive			
	Full Sear	2 11-decoycerticosterone-dő	(no adduct) 335.277	1 42	92	30	Positive	C1 Resolution (m/z)	2	
m Templates	Descurt Los Kear	1 11-decoycentical	(to adduct) 347.2217	1 435	0.2	50	Positive	CT Office	00	
		A 11-decorptortected	(no adducti 552.2531	1 435	92	30	Postere		1	
periments •	-SIM Stan	1 12-0H-P	(to adduct) 331.2268	1 501	0.2	82	Factive	Collision Energy Mode	fixed	
		4 11-06-8-85	(30 addort) - 335.277	1 500	92	\$2	Posture	Collision Energy Type	Assolute	
		7 Aldosterene	(to adjuct) - 355,1864	1 3.55	0.2	16	Negative	Collision finergy (V)		
	OlAster			1 3.59	.0.2	16	Negatore			
	OlA Set 1	Aldosterane-d?	110 adduct 366.2503						15000	
	OlA Serve:	1 Andrestenctione	(no adduct: 287,2006	1 425	02	30	Footive	Cristiap Recolution		
	Old School	1 Androstenctione 10 Androstenctione-dS	(% adduch 287,2006 (% adduch 280,27%	1 478	92	50	Poster	Cristup Recolution Scan Range Mode	Auto	
	OLA Seas	Andrestendione Andrestendione Andrestendione Andrestenene	(10 adduct: 287,2006 (10 adduct: 280,2794 (10 adduct: 277,2215	1 475 1 56	02 02	an M	Positive Positive	Scan Range Mode	1	
	CIASON:	Androstenctione Androstenctione Androstenctione Androstence Androstence Androstence	(10 addud) 287,2006 (10 addud) 280,2794 (10 addud) 273,2213 (10 addud) 277,2464	1 475 1 56 1 56	92 92 92	50 34 30	Poster Poster Poster	Scan Kange Mode	60.	
	CASter	Andrestendione Andrestendione Andrestendione Andrestendione Andrestenen Andrestenen Cetizaterene	(10.845ud; 287,2006 (10.8458ud; 270,2754 (10.8458ud; 277,2265 (10.8458ud; 277,2265	1 475 1 56 1 58 1 427	02 02 02 02	50 30 80 51	Poster Poster Poster Poste	Scan Range Mode	1	
	OASeas	Findepotencipione Andepotencipione Andepotencipione Andepotence Andepotence Andepotence Andepotence Sectionatione	No adduuti 201,2000 (no adduuti 200,2704 (no adduuti 207,2215 (no adduuti 277,2216 (no adduuti 277,2216 (no adduuti 277,2217 (no adduuti 355,2219	1 425 1 56 1 56 1 427 1 427	02 02 02 02 02 02	50 30 31 31 31	Positive Positive Positive Positive Positive	Scan Kange Mode	60.	
	OASews	E Abdiostencione Abdiostencione Abdiostencione Abdiostencio Abdiostencio Abdiostencio Abdiostencio Cettostencio Cettostencio Cettost Cettost	No. adduutt. 287.2000 No. adduutt. 270.2704 No. adduutt. 277.2706 No. adduutt. 277.2706 No. adduutt. 277.2706 No. adduutt. 272.217 No. adduutt. 257.2166 No. adduutt. 257.217 No. adduutt. 252.217 No. adduutt. 252.216 No. adduutt. 252.217	1 425 1 56 1 56 1 429 1 429 1 582	02 02 02 02 02 02 02	50 36 51 51 51 22	Poster Poster Poster Poster Poster Poster	Suan Range Mude PELoni (%) Maximum Injection Time Mode Doto Type	60. Auto Profile	
	OlAscan	F Andeostencione Andeostencione Andeostencione Andeostencione Andeostence Andeostence Andeostence Andeostence Andeostence Settost Settost Settost	1% adduud 283,2000 1% adduud 290,2764 1% adduud 272,213 1% adduud 272,208 1% adduud 272,208 1% adduud 282,271 1% adduud 383,2719 1% adduud 383,2719 1% adduud 382,2719 1% adduud 382,2716 1% adduud 382,2716	1 425 1 56 1 56 1 427 1 627 1 582 1 582	02 02 02 02 02 02 02 02 02 02	50 30 31 31 31 32 22	Positive Positive Positive Positive Positive Positive	Scan Range Mode RF Lan (%) Maximum Injection Time Mode Dec Type Polarty	60 Ayto Profile Communication	hi (
	Oldane	Androstendione Androstendione Androstendione Androstendione Androstendion Androstenend Caticateriane di Caticateriane di Caticate Caticat Caticat	1% 8450.05 250,2000 1% 8450.05 250,2004 1% 8450.05 270,2004 1% 8450.05 272,2004 1% 8450.05 247,2217 1% 8450.05 245,2217 1% 8450.05 345,2217 1% 8450.05 345,2219 1% 8450.05 345,2219 1% 8450.05 345,2219 1% 8450.05 345,2217 1% 8450.05 345,2217 1% 8450.05 345,2217 1% 8450.05 345,2217 1% 8450.05 345,2217 1% 8450.05 345,2217 1% 8450.05 345,2217	1 42% 1 56 1 56 1 429 1 629 1 58 1 582 1 582	02 02 02 02 02 02 02 02 02 02	50 50 51 51 52 52 52	Poster Fouter Poster Poster Poster Poster Poster	Suan Range Mude PELoni (%) Maximum Injection Time Mode Doto Type	60. Auto Profile	hi (
	Oldster	F Androstendione Androstendione Ja Androstendione Androstendione Androstendione Androstenon Andro	1% 6450.05 251.2005 1% existing 270.2161 1% existing 272.2163 1% existing 272.2163 1% existing 352.217 1% existing 352.217 <td>1 475 1 56 1 54 1 427 1 427 1 582 1 582 1 587 1 289 7 189</td> <td>02 02 02 02 02 02 02 02 02 02 02</td> <td>50 50 51 51 52 52 52 52 52</td> <td>Positier Positier Positier Positier Positier Positier Positier Positier Positier</td> <td>Scan Range Mode RF Lan (%) Maximum Injection Time Mode Dec Type Polarty</td> <td>60 Ayto Profile Communication</td> <td></td>	1 475 1 56 1 54 1 427 1 427 1 582 1 582 1 587 1 289 7 189	02 02 02 02 02 02 02 02 02 02 02	50 50 51 51 52 52 52 52 52	Positier Positier Positier Positier Positier Positier Positier Positier Positier	Scan Range Mode RF Lan (%) Maximum Injection Time Mode Dec Type Polarty	60 Ayto Profile Communication	
	OA556	Androstensbore Androste	Inc. Status Status Status Inc. Adduct 270,2744 Inc. Adduct 270,2215 Inc. Adduct 272,2484 Inc. Adduct 372,2484 Inc. Adduct 382,2717 Inc. Adduct 382,2716 Inc. Adduct 382,2716 Inc. Adduct 382,2716 Inc. Adduct 382,2717 Inb. Adduct 382,2717 Inb. Adduct 382,2717 Inb. Adduct 384,2717 Inb. Adduct 384,2717 <td< td=""><td>1 4/5 1 56 1 56 1 42 1 427 1 52 1 582 1 582 1 587 1 589 1 589 1 589</td><td>02 02 02 02 02 02 02 02 02 02 02 02 02 0</td><td>50 30 31 31 22 22 32 32 32 32 32 32</td><td>Postler Foutie Postler Postler Postler Postler Postler Postler Postler</td><td>Saan Range Mode 89 Euns (%) Maximum Injection Time Mode 00 Des Type 9 Polanty Source Fragmanilation</td><td>60. Astro Profile Symmetry (10)</td><td></td></td<>	1 4/5 1 56 1 56 1 42 1 427 1 52 1 582 1 582 1 587 1 589 1 589 1 589	02 02 02 02 02 02 02 02 02 02 02 02 02 0	50 30 31 31 22 22 32 32 32 32 32 32	Postler Foutie Postler Postler Postler Postler Postler Postler Postler	Saan Range Mode 89 Euns (%) Maximum Injection Time Mode 00 Des Type 9 Polanty Source Fragmanilation	60. Astro Profile Symmetry (10)	
	OA556	8 Autostructioned E 10 Autostructioned E 11 Autostructioned E 12 Autostructioned E 13 Concentrone 14 Concentrone 15 Concentrone 16 Concentrone 17 Concentrone 18 Concentrone 19 Concentrone 10 Concentrone 10 Concentrone 11 Concentrone 12 Concentrone	No.455.01 20.205 No.455.01 20.216 No.455.01 27.215 No.455.01 27.217 No.455.01 28.219 No.455.01 28.219 No.455.01 28.217 No.455.01 28.216	1 435 1 56 1 54 1 427 1 382 1 382 1 587 1 587 1 190 1 323	02 02 02 02 02 02 02 02 02 02 02	50 50 51 51 52 52 52 52 52	Positier Positier Positier Positier Positier Positier Positier Positier Positier Positier	Saan Range Mode 89 Euns (%) Maximum Injection Time Mode 00 Des Type 9 Polanty Source Fragmanilation	60. Astro Profile Symmetry (10)	
	OASSN:	8 Advantant Market 10 Advantant Market 11 Advantant Market 12 Advantantantantantantantantantantantantanta	Pa-adduct, 201300 Yea-adduct, 201304 Yea-adduct, 272,215 Yea-adduct, 272,215 Yea-adduct, 272,216 Yea-adduct, 272,217 Yea-adduct, 272,218 Yea-adduct, 272,218 Yea-adduct, 272,218 Yea-adduct, 272,218 Yea-adduct, 282,217 Yea-adduct, 217,2108	1 435 1 56 1 54 1 427 1 427 1 58 1 58 1 587 1 587 1 589 1 588 1 588	02 02 02 02 02 02 02 02 02 02 02 03 03 02 02 02 02 02	00 30 31 35 35 32 32 32 32 32 32 32 32 32 32 32 32 32	Positive Pos	Saan Range Mode 89 Euns (%) Maximum Injection Time Mode 00 Des Type 9 Polanty Source Fragmanilation	60. Astro Profile Symmetry (10)	
	Öldise	8 Autostructioned E 10 Autostructioned E 11 Autostructioned E 12 Autostructioned E 13 Concentrone 14 Concentrone 15 Concentrone 16 Concentrone 17 Concentrone 18 Concentrone 19 Concentrone 10 Concentrone 10 Concentrone 11 Concentrone 12 Concentrone	No.455.01 20.205 No.455.01 20.216 No.455.01 27.215 No.455.01 27.217 No.455.01 28.219 No.455.01 28.219 No.455.01 28.217 No.455.01 28.216	1 435 1 56 1 54 1 427 1 382 1 382 1 587 1 587 1 199 1 325	02 02 02 02 02 02 02 02 02 02 02 03 03	50 50 51 22 22 52 52 52 52 52 52 52 52 52 52 52	Positier Positier Positier Positier Positier Positier Positier Positier Positier Positier	Saan Range Mode 89 Euns (%) Maximum Injection Time Mode 00 Des Type 9 Polanty Source Fragmanilation	60. Astro Profile Symmetry (10)	

Move from method set up to analysis quickly using ready-to-use application-specific templates.

Report actionable results faster using powerful data analysis tools


Providing reportable results in a timely manner requires access to a truly connected data processing ecosystem. Regardless of application, Thermo Scientific small-molecule data analysis solutions streamline unknown identification, screening, and quantitation using a powerful suite of tools.



Compound Discoverer software

Small-molecule unknown identification

- Confidently identify unknowns faster with spectral library searching using the online mzCloud mass spectral library, offline Thermo Scientific[™] mzVault[™] spectral libraries and searchable on-line 3rd party libraries
- Efficiently rank putative candidates with the Thermo Scientific[™] mzLogic[™] data analysis algorithm
- Specify desired data flows with drag-and-drop workflow nodes
- Review only data you choose with customizable data visualization



Unknown screening results shown with an integrated view in Compound Discoverer software, including raw data, chromatographic peak, and mass spectrum (including mirror plot with mzCloud match).

m/z CLOUD

Thermo Scientific[™] mzCloud[™] mass spectral library

- Extensive, high-quality spectral fragmentation library
- Chemically diverse, covering all applications
- Fully integrated with Thermo Scientific[™] Compound Discoverer[™] software
- Available offline via mzVault for Thermo Scientific[™] TraceFinder[™] software



TraceFinder software

High-throughput screening and quantitation

- Save time training staff using a single platform for both screening and quantitation
- View only desired data parameters with a customizable user interface
- Efficiently analyze and report data with customizable flagging and report templates

Dat	ta Kentenn - S	impleQuart_1 (Quart)*					_			_				_	_				_		_
0-	(the second		Sample	Results											_					- 4	×
1	Compound	Compound Type	10 24	Flags	Status	Sample Type	-	Flag Details	Fierane	Level	Area	ISTO Response	Response Ratio	Expected RT	Actual RT	RT Delte	Calculated Ant	Theoretical Amt	Th EV	n.ASD	-
	e .				de	80 T.	- 24		81 4	41.10	40 -			50 ×		4 .	a		a		
1	Analyte	Target Compound	10	2 🗯	•	Cal Stal	-8		20pg	.20	4543	05645	0.069	107	3.06	-0.62	26.799	20.000	5.71	4.02	
2	Internal Standa	of Standard Standard	7	3	•	Cal Still			50pg	30	10094	67985	0.162	3.07	3.06	-0.03	52.452	50.000	2.87	2.02	
	-		1	4 🐂	•	Cai Stal			200pm	100	20853	63999	0.326	3.07	3.09	-0.02	97,591	100.000	3.06	2.81	
	Feld CRootes		4	5 🗮	•	Cal Std			250pg	250	62980	80682	0.781	307	3.05	-0.02	223.041	250.000	7.35	7.35	
	197	4 CV	5	8 P	•	Cal Std			500pg	500	14,7900	#1642	2.763	3.07	105	-0.02	493.920	500,000	3.46	3.42	
	181	100	4 3		•	Cai Set	*		20pp#	20	4023	64675	0.042	2.07	1.05	-0,01	24.869	20.000	\$71	4.02	15
	12	SASD-	7 1	4 .	•	Car Stell			50,098	50	6602	42252	0.150	3.07	3.05	-0.01	50.809	50.000	2.37	2.02	
	197	Artive	8 1	5 🗯	•	Cai Stat			100pge	100	27476	55274	0.316	3.07	3.09	-0.01	94.825	200,000	3.06	2.81	
	12	-Actual 81	4 1	a 🦷		Cal Stat			250pga	250	5355W	63063	0.681	3.07	3.06	-0.01	250.740	250.000	7.35	7.33	
	12	Adduct	10 1		•	Call Stat			500pq#	500	15352#	62019	1.672	3.07	3.06	-0.01	524.071	500.000	3.48	3.42	
	12	Ires	11 1	a 🗯	•	Cal Stel	A		20pgb	20	4581	67108	0.066	107	3.06	-0.01	26.541	25,000	5.71	4.02	
	12	Batch Orden	12 . 2	10 💻	•	Cw Still			50090	50	6665	40929	0.163	3.07	349	-0.62	\$2.767	30.000	2.37	2.02	
		Calculated Annt	13 2		•	Cal Pol			203e-git	100	12918	45477	0.305	3.07	3.05	-0.02	92.254	300.000	3.06	2.81	
	10	Channel	14 .2		•	Cal Stat			250pgb	-250	45593	50905	0,896	3.07	3.06	-0.01	254.775	250.000	7.35	7.11	
		Conmants	15 .7		•	Cel Stat			500pgb	500	137583	75027	1.764	3.07	3.07	0.00	494.445	500,000	3.48	1.42	
	£1		16	2 10	•	Matter Glark			ISBI		10	70895	0.001	2.07	2.91	-0.14	7.974	N/A	NA	N/4	
	12	Cortino .	17	7	•	Matrix Blank			1584		63	70845	0.002	3.07	2.93	42.0-	7,974	11/A	#4/A	PL/A	
			1	-		Alexandra Province	_		1986		- 10 m		- n mm	.kerr.	101.	PLS P	2.0156		4)/4	10	
	paned Details			1=	*					* ×	Californian Cu									- 9	0
See.	Peak.					firming Jons	÷			and the second	, and rapidly C.				-					w ×	
10	og Analyta m	05.07.300			Spec	(Sre procedus	(First		1.1	1 2			Y = 1.6	25e-3X - 2.795e	2 11-2 0.98	A, Origini Ry	see, W. Smith Area				
		RT 3.05			Jam J	Overlay	1	All 2.24 Ad. 24425.54			4										
		AA: 3349.32 AH: 1566.30			Late	(g.		Ann: 44552 14			1.6-									1	
	100]	AN ISES A				ary Match		4											/	-	
	99-	Δ.			Fate	trence Peak					18-							/			
	80-				11.1	42-		11			14										
18	70-				110	[m]		11									/				
- 2	60-				1123	40-		13			12-						/				
15					- 113	1					8										
-8	10-					4.5					£ 10-					/					
	40-					200		1			2				1						
	30-					192-1								1							
	23/10	LA III.									0.0-			/							
	10-	~~~ V	have	~			-			2	4		/								
	ail		· · · · ·					30 43			0.4-		-								
	- country	29 3.0 3.1 RTimmi	32	33				HT[mir]		- 11	02-	-	-								
	/# 97.300	Bitoming			- 10						-	-									
A	ra: 97.300 pex RTI - 3.05	Len RT: 3.02 Kight RT:	130			pex #1/3.04 /ea:94430				1	0.0										
-				_							0	80	106 180	990	540	300		-650	sio.	100	

Rearrange flexible data-review panes to customize columns, plot layouts, and positioning of content. Quickly and easily observe data processing status, view compound-related flags to locate compounds which need attention, and take appropriate steps to correct any problems.



Thermo Scientific[™] Chromeleon[™] Chromatography Data System (CDS) software


Enterprise-ready, regulatory-compliant quantitation

- Streamline chromatography and MS software training using the first CDS with quantitative MS analysis control
- Prepare for audits confidently with support for GLP, CMP, and 21 CFR Part 11 regulations
- Connect multiple sites and locations to a central data center with network failure protection
- Easily connect to third-party software applications and multi-vendor LC and GC chromatography instruments



Fourth-generation quadrupole-Orbitrap mass spectrometer

The Orbitrap Exploris 120 mass spectrometer combines proven technology refined over more than 20 years with advanced performance and speed capabilities, day-to-day reliability, and a compact footprint. Now both novice and expert high-resolution MS users can efficiently deploy the instrument to obtain highly reliable and accurate results.



Operationally streamline your laboratory with the Thermo Scientific ion and liquid chromatography portfolio

Ion chromatography (IC)

Recent innovations in the Thermo Scientific[™] Dionex[™] Ion Chromatography portfolio include high-pressure systems, 4 micron (µm) columns, and capillary IC systems. By choosing the technology leader in IC for over 40 years, you can be confident you're investing in the best ion analysis solution.



Thermo Scientific™ Dionex™ ICS-6000 HPIC™ system



Thermo Scientific™ Dionex™ Aquion™ IC system



Thermo Scientific[™]

Dionex[™] Integrion[™]

HPIC[™] system



Thermo Scientific™ Dionex™ ICS-4000 Capillary HPIC™ system

Liquid chromatography (LC)

Invest in the innovative, proven Thermo Scientific[™] Vanquish[™] HPLC and UHPLC systems to separate your science from the status quo.











Thermo Scientific[™] Vanquish[™] Horizon UHPLC System



Thermo Scientific[™] Vanquish[™] Flex UHPLC system

thermo scientific

Almanac web-based monitoring and management

Stay connected to your science. See how the Thermo Scientific[™] Almanac[™] application can help you get the most out of your instruments.

thermofisher.com/almanac



Technical and online support: peak performance for your instruments

Helping you keep your instruments running at peak performance is our goal. Whether you're looking for an instrument manual or spare parts, want to submit a repair request, or check on the status of your warranty or service contract, we have every support option you're looking for.

thermofisher.com/technicalresources

Protecting your investments: unparalleled laboratory services

Unity[™] Lab Services provides a single source for integrated lab service, support, and supply management. Our customized service offerings and world-class service experts have the flexibility and experience to address your laboratory's needs. We provide a complete portfolio of services and support solutions designed to help you improve productivity, reduce total cost of ownership, and ensure performance throughout your laboratory. unitylabservices.com

Thermo Scientific TraceFinder software thermofisher.com/TraceFinder

Thermo Scientific Compound Discoverer software thermofisher.com/CompoundDiscoverer

Thermo Scientific mzCloud mass spectral library thermofisher.com/mzCloud

Thermo Scientific Chromeleon CDS software thermofisher.com/Chromeleon

Find out more at thermofisher.com/OrbitrapExploris120

For Research Use Only. Not for use in diagnostic procedures. © 2020 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. This information is presented as an example of the capabilities of Thermo Fisher Scientific products. It is not intended to encourage use of these products in any manners that might infringe the intellectual property rights of others. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representatives for details. BR65656-EN 0620M

